



SPEED QUEEN® ON-PREMISES LAUNDRY SOLUTIONS

Front Control Single Dryer

LDEE5BGS173TW01, LDGE5BGS113TW01

Single Dryers

With an easy-to-clean large lint compartment and a reversible door to accommodate your laundry design, Speed Queen® single dryers are designed to suit your laundry's specific needs. The 2.06 sq. ft. door opening is the largest in the industry, providing easy loading and unloading.

- Durable galvanized steel cylinder with an extra-large 7 cu. ft. of volume.
- Efficient dryer heating with 22,500 Btu (gas models) and 5350 Watts (electric models).




Electronic Homestyle Control

Speed Queen® dryers with Electronic Homestyle controls are designed for durability and are easy to operate with intuitive selection buttons and cycle status indicator lights. This control option features a time-remaining display, six preset cycle buttons, cycle adjustability for temperature and load size.

Front Control Single Dryer

| Specifications | | |
|--|--|------------------|
| Model | LDEE5BGS173TW01, LDGE5BGS113TW01 | |
| Control Option | Electronic Homestyle | |
| Control Location | Front | |
| Capacity - lb (kg) | 18 (8.2) | |
| Cylinder Volume - cu. ft. (liters) | 7.0 (198) | |
| Overall Width - in (mm) | 26.875 (683) | |
| Overall Depth - in (mm) | 28 (711) | |
| Overall Height - in (mm) | 40.42 (1027) | |
| Motor Power Consumption - hp (kw) | 0.33 (0.25) | |
| Available Heat Sources | Gas or Electric | |
| Available Heating Element (Electric W) | 5350 @ 240V | |
| Gas Inlet Connection - in (mm) | 3/8 (9.5) | |
| Gas Consumption - BTU/Hr | 22,500 | |
| Exhaust Outlet Dia. - in (mm) | 4 (102) | |
| Exhaust Airflow - cfm (liters/sec) | 220 (105) | |
| *Available Cycles | Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up | |
| Cycle Indicator Lights | Yes | |
| Cylinder Finish | Galvanized | |
| Available Colors | White | |
| Door Type (Solid/Window) | Solid | |
| Available Electrical Requirements - Voltage/Hz/Ph - Circuit Amperage | Electric | 120/240/60/1 -30 |
| | Gas | 120/60/1 - 15 |
| Shipping Dimensions Approx. - in (mm) | Width | 29.5 (749) |
| | Depth | 30.5 (775) |
| | Height | 45 (1143) |
| Net Weight - lb (kg) | Electric | 126 (57) |
| | Gas | 130 (59) |
| Shipping Weight - lb (kg) | Electric | 136 (62) |
| | Gas | 140 (64) |
| Agency Approvals | Electric | cULus |
| | Gas | cCSAus |



| | |
|-----------------------------------|--------------|
| A. Overall Width - in (mm) | 26.875 (683) |
| B. Overall Depth - in (mm) | 28 (711) |
| C. Overall Height - in (mm) | 40.42 (1027) |
| D. Floor To Door Opening -in (mm) | 15.44 (392) |
| E. Door Swing - in (mm) | 23.5 (597) |

ADA Compliant

Note: Not all options are available for all models. Refer to the price list for the available models and options.

* Information shown applies to highest end control available.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.